PEMBROKE INSTRUMENTS, LLC

SWIR CAMERA DATA SHEET

HiPe SenS 640M ST

Manufacturer: New Imaging Technologies (NIT)

Technical data reproduced from the original manufacturer datasheet.

For a quote or more information email

sales@pembrokeinstruments.com

Ordering Information

Commercial Reference

Commercial reference	Description	Ordering information
HiPe SenS 640M-ST	HiPe SenS 640 Cameralink	9SMC1902AT31MI0# #: product revision, A or higher

Included Accessories

- Power and trigger Cable (Hirose HR10 connector)
- NITVision GUI/NITLibrary SDK
- Cardboard shipping and storage box

Optional Accessories

- Hardened protective case

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

FUNCTIONALITIES

Camera

Main camera features (For full documentation contact):


Sensor characteristics	Sensor type	InGaAs (0.9-1.7 spectral response, see QE curve)
	Pixel pitch	$15\mu m$
	Resolution	640x512
	Sensor diagonal	12.3mm
	Sensor noise	• High gain (CDS): <40e^- • Medium gain: <95e^- • Low gain: < 185e^-
	Full well capacity	• High gain (CDS): <15ke^- • Medium gain: <122ke^- • Low gain: < 315ke^-
	Dynamic range	• High gain (CDS): 52dB typical • Medium gain: 62dB typical • Low gain: 64dB typical
	Dark current	<2500 $e^-.pixel^{-1}.s^{-1}$; 2000 $e^-.pixel^{-1}.s^{-1}$ typical @-15°C FPA Temperature <1500 $e^-.pixel^{-1}.s^{-1}$; 1200 $e^-.pixel^{-1}.s^{-1}$ typical @-20°C FPA Temperature
	Peak QE	>85% (90% typical)
Camera features	Frame rate	>200Hz (full frame)
	Sensor Readout	Global shutter ITR (Integrate Then Read) and IWR (Integrate While Read)
	Sensor modes	3 modes: Linear Low Gain, Linear Medium Gain and Linear High Gain with CDS
	Output Type	14 bits pixel format
	Exposure time	Minimum Integration time: 10us Controlled by camera register or Trigger width
	Trigger	Internal/External (LVTTL) Software Trigger
	Trigger delay	User-Selectable
	Partial reading mode	Region of Interest (ROI). User-Selectable with a step of 8 pixels Maximum FPS increase with reduced ROI
Software (Processing on host system)	NIT Software	NITVision GUI (Windows/Linux, x64/aarch64 platforms) NITLibrary SDK (Windows/Linux, x64/aarch64 platform, C++ language) NIT software for this model is only compatible with Teledyne Dalsa frame grabbers
	AGC (Histogram Stretching)	Automatic/Manual Automatic: continuous offset and gain adjustment based on current image histogram User Selectable parameters: % pixels to ignore, ROI Manual: User-Selectable low and high limits
	NUC correction	Correction 1-Point or 2-Point. 2 Point factory calibrated @-15°C sensor temperature
	Bad pixel correction	Factory calibrated Bad Pixel Map
	Temperature monitoring	Image Sensor
	Image Flip	Horizontal/Vertical
	Image recording	JPEG, PNG, TIFF
	Video recording	AVI, PTW


*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Environment and mechanical characteristics	Power consumption (12V supply)	• Camera: <2.5W • Cooling (Sensor TEC + Air Cooling): ○ <15W
	Storage temperature	-10°C to +80°C
	Operating temperature	0°C to +65°C
	Size (WxHxL, mm)	57x46x105.5
	Weight	<350g
	Lens mount	C-Mount

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

QE Curve (typical)






*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Electrical ICD (M-ST – SDR26 video output)

Reference	Designation	Manufacturer
HR10-10R-12SA	12 pins female connector	Hirose




Reference	Designation	Manufacturer
12226-1150-00FR	SDR26 connector	3M

Hirose Connector Pinout		
Pin	Signal Name	Cable color
1	Power (6-24V)	Red/Purple/(Orange)
2	Power GND	Blue/Brown
3	Trigger OUT2	White
4	Trigger OUT1	Yellow
5	NC	
6	NC	
7	Reserved	
8	Power GND	Blue/Brown
9	Power (6-24V)	Red/Purple/(Orange)
10	Trigger IN/OUT (LVTTL)	Green
11	Not connected	
12	Trigger GND	Black

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Mechanical ICD (HiPe SenS 640 M-ST)



Gen. Tol. : - All dimensions are in mm						
Surface Finishing : -						
Treatment : -						
Material : -						
Designer : Christophe HABRE Date : 11/09/2020	A4	A Rev.	11/09/2020 Date	Creation MODIFICATION	VN Check	CH Author
1-4 impasse de la noisette, Bat D, 1er Etage, FRANCE - 91370 Verrières le buisson Tel : +33 1 64 47 88 58 www.new-imaging-technologies.com						SCALE
			Doc. Ref. : 9SMC1601AT31MI0A		REV. A	SHEET 1/1

Information contained in this document is the property of NEW IMAGING TECHNOLOGIES and is communicated confidentially for a specific matter.
The receiver is in charge of this document and ensures that it will not be either copied or reproduced in all part, and that the content will not be disclosed in any way to anybody except for its proper use.
The receiver is in charge of destroying any previous revision of this document in his possession.

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.


PEMBROKE
INSTRUMENTS
Imagining a Brighter Tomorrow
Advanced
Imaging Solutions
for a Smarter World
greateyes
CHARLIE
Avenir
PHOTONICS
ARIS
Compact USS spectrometer
NYLIS
High resolution spectrometer
pembrokeinstruments.com
sales@pembrokeinstruments.com
+1-650-550-8618
CAMERAS | SPECTROMETERS | IMAGING SOLUTIONS