PEMBROKE INSTRUMENTS, LLC

SWIR CAMERA DATA SHEET

WIDY SenS 320ML ST

Manufacturer: New Imaging Technologies (NIT)

Technical data reproduced from the original manufacturer datasheet.

For a quote or more information email

sales@pembrokeinstruments.com

Ordering Information

Commercial Reference

Commercial reference	Description	Ordering information
WiDy SenS 320M-ST	WiDy SenS 320 Cameralink (QVGA) **SDR26 & HR10-10R connector**	9SMC2001AS31MC0# #: **product revision, C or higher**
WiDy SenS 320L-ST	WiDy SenS 320 Cameralink (QVGA) **LSHM130 connector**	9SMC2001AS31LC0# #: **product revision, A or higher**

Included Accessories

- Power and trigger Cable (Hirose HR10 connector)
- NITVision GUI/NITLibrary SDK
- Cardboard shipping and storage box

Optional Accessories

- Heatsinks
- Hardened protective case

Custom variants (OEM)

Various options may be available depending on your camera model:

- Open frame housing
- Sensor without cover glass
- Flex configuration (sensor board split from camera electronics)
- …

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

FUNCTIONALITIES

Camera

Main camera features (For full documentation contact):

Sensor characteristics	Sensor type	InGaAs (0.9-1.7 spectral response, see QE curve)
	Pixel pitch	$15\mu m$
	Resolution	320x256
	Sensor diagonal	9.1mm
	Sensor noise	• High gain (CDS): <50e^- • Low gain: < 270e^- • Log: <340e^-
	Dynamic range	• High gain (CDS): 49dB typical • Low gain: 63dB typical • Log: 120dB typical
	Peak QE	>70%
Camera features	Frame rate	>800Hz
	Sensor Readout	Global shutter ITR (Integrate Then Read) and IWR (Integrate While Read)
	Sensor modes	4 modes: Log, Linear Low Gain, Linear High Gain and Linear High Gain with CDS
	Output Type	14 bits pixel format
	Exposure time	Minimum Integration time: 10us (Linear) / 100us (Log) Controlled by camera register or Trigger width
	Trigger	Internal/External (LVTTL) Software Trigger
	Trigger delay	User-Selectable
	Partial reading mode	Region of Interest (ROI). User-Selectable with a step of 8 pixels Maximum FPS increase with reduced ROI
Software (Processing on host system)	NIT Software	NITVision GUI (Windows/Linux, x64/aarch64 platforms) NITLibrary SDK (Windows/Linux, x64/aarch64 platform, C++ language) NIT software for this model is only compatible with Teledyne Dalsa frame grabbers
	AGC (Histogram Stretching)	Automatic/Manual Automatic: continuous offset and gain adjustment based on current image histogram User Selectable parameters: % pixels to ignore, ROI Manual: User-Selectable low and high limits
	NUC correction	Correction 1-Point or 2-Point. 2 Point factory calibrated @25°C sensor temperature
	Bad pixel correction	Factory calibrated Bad Pixel Map
	Temperature monitoring	Image Sensor
	Image Flip	Horizontal/Vertical
	Image recording	JPEG, PNG, TIFF
	Video recording	AVI, PTW


*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Environment and mechanical characteristics	Power consumption (12V supply)	• Camera: <2.5W
		• Cooling: User-Selectable TEC power limit
		  ○ Off
		  ○ Low: <1Ws
		  ○ Medium: <2W
		  ○ High: <4W

	Supply voltage range	6 to 15V, 12V nominal (Overvoltage, reverse polarity protection). PoCL available upon request
	Storage temperature	-10°C to +80°C
	Operating temperature	-10°C to +65°C
	Size (WxHxL, mm)	46x46x59.7 (M-ST) / 49 (L-ST) 90x46x59.7 with heatsinks
	Weight	<215g <315g with heatsinks
	Lens mount	C-Mount


*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

QE Curve (typical)



*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Electrical ICD (M-ST – SDR26 video output)



Reference	Designation	Manufacturer
HR10-10R-12SA	12 pins female connector	Hirose


Reference	Designation	Manufacturer
12226-1150-00FR	SDR26 connector	3M

Power supply possible via the HR10 connector or the SDR26 with PoCL (available on request).

Hirose Connector Pinout		
Pin	Signal Name	Cable color
1	Power (6-24V)	Red/Purple/(Orange)
2	Power GND	Blue/Brown
3	Trigger OUT2	White
4	Trigger OUT1	Yellow
5	NC	
6	NC	
7	Reserved	
8	Power GND	Blue/Brown
9	Power (6-24V)	Red/Purple/(Orange)
10	Trigger IN/OUT (LVTTL)	Green
11	Not connected	
12	Trigger GND	Black

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Electrical ICD (L-ST – LSHM130 output)




Reference	Designation	Manufacturer
12226-1150-00FR	SDR26 connector	3M

Pin Number	Name	Type	Comment	Pin Number	Name	Type	Comment
1	GND	Power	Supply voltage groun	31	NC		
2	GND	Power	Supply voltage groun	32	NC		
3	CamLinkPair4+	Clock		33	NC		
4	CamLinkPair5+	Data3		34	Trigger Out	TTL	Programmable
5	CamLinkPair4-	Clock		35	NC		
6	CamLinkPair5-	Data3		36	Trigger Out	TTL	Programmable
7	GND			37	NC		
8	GND			38	Trigger In/Ou	TTL	Programmable
9	CamLinkPair3+	Data2		39	GND		
10	CamLinkPair2+	Data1		40	GND		
11	CamLinkPair3-	Data2		41	NC		
12	CamLinkPair2-	Data1		42	NC		
13	GND			43	NC		
14	GND			44	NC		
15	CamLinkPair1+	Data0		45	Cable detect		100 Ohm to GND
16	NC			46	NC		
17	CamLinkPair1-	Data0		47	Enable		On : 1.6 to 3.3V or floating Off: Connect to GND to turn off
18	NC			48	NC		
19	GND			49	GND		
20	GND			50	GND		
21	CamLinkPair7+	SerTG		51	GND		
22	CamLinkPair8+	CC1		52	GND		
23	CamLinkPair7-	SerTG		53	GND		
24	CamLinkPair8-	CC1		54	GND		
25	CamLinkPair6+	SerTC		55	Power Input	Power	9 to 35V
26	CamLinkPair9+	CC2		56	Power Input	Power	9 to 35V
27	CamLinkPair6-	SerTC		57	Power Input	Power	9 to 35V
28	CamLinkPair9-	CC2		58	Power Input	Power	9 to 35V
29	GND			59	Power Input	Power	9 to 35V
30	GND			60	Power Input	Power	9 to 35V

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Mechanical ICD (WiDy SenS 320 M-ST)



Gen. Tol. : +/- 0.100000mm All dimensions are in mm		E				
Surface Finishing: Black Anodization		D				
Treatment: Surtec 650		C				
Material: Aluminium 7075		B				
Designer: VN	A4	A	29/09/2022	Creation	Check	VN
Date: 29/09/2022		Rev.	Date	Modification	Check	Author

1-4 impasse de la noisette,
Bat D, 1er Etage,
FRANCE - 91370 Verrières le buisson
Tel : +33 1 64 47 88 58
www.new-imaging-technologies.com

SCALE 1:1

Doc. Ref. : Widy SenS 320 M-ST


REV. A

SHEET 1/1

Information contained in this document is the property of NEW IMAGING TECHNOLOGIES and is communicated confidentially for a specific matter.
The receiver is in charge of this document and ensures that it will not be either copied or reproduced in all part, and that the content will not be disclosed in any way to anybody except for its proper use.
The receiver is in charge of destroying any previous revision of this document in his possession.

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.

Mechanical ICD (WiDy SenS 320 L-ST)



*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change by NIT without notice.
Products are only warranted by NIT to meet NIT's production data sheet specifications.


PEMBROKE
INSTRUMENTS
Imagining a Brighter Tomorrow
Advanced
Imaging Solutions
for a Smarter World
greateyes
CHARLIE
Avenir
PHOTONICS
ARIS
Compact USS spectrometer
NYLIS
High resolution spectrometer
pembrokeinstruments.com
sales@pembrokeinstruments.com
+1-650-550-8618
CAMERAS | SPECTROMETERS | IMAGING SOLUTIONS